

# DTS-LED TWIN

illuminazione a LED  
per macchinari  
Machinery LED lighting



IP65

-25 +40  
°C

CE

RoHS  
COMPLIANT

| MODELLI<br>Model List | Codice<br>Code | Potenza<br>Power | Tensione<br>d'ingresso<br>Input voltage | Flusso<br>luminoso<br>Luminous flux | Fascio<br>luminoso<br>Beam | Dimensioni<br>Case size W x H x D | Peso<br>Weight |
|-----------------------|----------------|------------------|---|-------------------------------------|----------------------------|-----------------------------------|----------------|
| DTS-LED TWIN          | 3479000699     | ○ 45 W<br>● 45 W | 24 VDC                                  | ○ 2482 lm<br>● 1256 lm              | 50° x 16°                  | 1000 x 46 x 38 mm                 | 2300 g         |

|  |                                       |
|--|---------------------------------------|
| Grado di protezione / Protection level       | IP65                                  |
| Temperatura operativa<br>Working temperature | -20...+40 °C                          |
| CCT  | ○ 4000 K                              |
| CRI  | ≥80%                                  |
| Modalità di montaggio<br>Mounting method     | Fissaggio con viti<br>Fixed by screws |

| Colore LED / LED Colour | Collegamento / Wiring |
|-------------------------|-----------------------|
| ○                       | — +<br>— -            |
| ●                       | — +<br>— -            |



## Dimensioni / Dimensions

