



DTS-LED ARM-4 / DTS-LED SPOT-4




IP65



PIN nr.	LED
1	+
3	-



DIMENSIONI - Dimensions [mm]



MODELLI Models	Codice Code	Assorbimento Power cons.	Tensione d'ingresso Input voltage	Fascio luminoso Beam	Ø Faretti Ø Lamp	Peso Weight
DTS-LED ARM-4	3470200008	5 W	24 VDC $\pm$ 15%	45°	Ø 59 mm	440 g
DTS-LED SPOT-4	3470200009		24 VDC stab. $\pm$ 3%			200 g

Grado di protezione - Protection level	IP65
Efficienza luminosa - Luminous efficiency	75 lm/W
Temperatura operativa Operating temperature	<60°
Durata - Lifespan	50000 h
CCT	6000-6500K
CRI	>82Ra
Corpo Housing	Lega di alluminio Aluminum alloy
Modalità di montaggio Mounting method	Base fissa Fixed base
Interruttore - Light switch	Incorporato - Incorporated (ARM-4)
ingresso alimentazione Power supply input	(ARM-4) cavo 2m - 2 mt cable (SPOT-4) connettore M12 4 poli maschio - M12 connector 4 poles male

Altezza Height	Area	LUX max. / med.
1 m	Ø 0.60 m	1420 928
2 m	Ø 1.15 m	355 232
3 m	Ø 1.70 m	158 103
4 m	Ø 2.30 m	89 58
5 m	Ø 2.90 m	57 37

CURVE FOTOMETRICHE - Photometric data

